



Technische Informatie Complete wielen voor aanhangwagens en caravans



Wiel compleet



Artikel-Nr.	Maatvoering	LI	Profiel	Merk	Wiel	Aansluitmaat	ET	Draagvermogen kg	Hoogte mm	Breedte mm
599.51.005	4.00 - 8	70 N	B-61	Sava	2.50 x 8	4/57/100	0	335	419	107
599.51.020	5.00 - 8	77 M	KT-701	Diverse	3.00 x 8	4/57/100	0	412	423	125
599.51.025	5.00 - 10	78 N	B-61	Sava	3.50 x 10	4/57/100	0	425	517	141
596.00.010	145 R 10	74 N	CR-966	Trailermaxx	3.50 x 10	4/57/100	0	375	492	147
599.54.100	135/80 R 13	74 N	BK-403	Security	4 J x 13	4/57/100	30	375	546	133
596.00.092	145/80 R 13	78 N	BK-403	Security	4 J x 13	4/57/100	30	425	572	145
596.00.094	145/80 R 13	78 N	BK-403	Security	4 J x 13	5/67/112	30	425	572	145
599.96.060	155/70 R 13	79 N	Bk-403	Security	4 J x 13	4/57/100	30	437	556	158
599.96.026	155/80 R 13	84 N	BK-403	Security	4 J x 13	4/57/100	30	500	578	157
599.96.058	155/80 R 13	84 N	BK-403	Security	4 J x 13	5/67/112	30	500	578	157
599.96.015	155/80 R 13	84 N	CR-966	Trailermaxx	4 J x 13	4/57/100	30	500	581	157
599.96.053	155/80 R 13	84 N	CR-966	Trailermaxx	4 J x 13	5/67/112	30	500	581	157
596.00.112	165/70 R 13	84 N	BK-403	Security	4 J x 13	4/57/100	30	500	572	172
596.00.111	165/70 R 13	84 N	BK-403	Security	4 J x 13	5/67/112	30	500	572	172
599.96.032	175/70 R 13	86 N	BK-403	Security	4 1/2 J x 13	4/57/100	30	530	576	177
599.96.034	175/70 R 13	86 N	BK-403	Security	4 1/2 J x 13	5/67/112	30	530	576	177
596.00.128	185/70 R 13	90 N	BK-403	Security	5 J x 13	4/57/100	30	600	600	189
596.00.130	185/70 R 13	90 N	BK-403	Security	5 J x 13	5/67/112	30	600	600	189
599.55.229	165/70 R 14 RF	85 N	MA-701	Maxxis	5 J x 14	4/57/100	30	515	598	177
599.55.230	165/70 R 14 RF	85 N	MA-701	Maxxis	5 J x 14	5/67/112	30	515	598	182
597.38.013	175/70 R 14 RF	88 N	MA-701	Maxxis	5 J x 14	4/57/100	30	500	612	189
597.38.012	175/70 R 14 RF	88 N	MA-701	Maxxis	5 J x 14	5/67/112	30	500	612	189
597.38.016	185/60 R 14	82 N	-	Diverse	5 1/2 J x 14	5/67/112	30	475	586	197
596.38.030	185/65 R 14 RF	93 N	BK-403	Security	5 1/2 J x 14	5/67/112	30	650	600	192
597.38.050	185/65 R 14 RF	93 N	CR-965	Trailermaxx	5 J x 14	4/57/100	30	600	600	192
597.38.030	185/65 R 14 RF	93 N	CR-965	Trailermaxx	5 1/2 J x 14	5/67/112	30	650	600	192
599.96.065	185/70 R 14	88 N	MA-701	Maxxis	5 1/2 J x 14	5/67/112	30	560	626	197
597.38.071	195/65 R 14	90 N	UA-603	Maxxis	5 1/2 J x 14	5/67/112	30	530	600	204
597.58.058	195/70 R 14	96 N	BK-403	Security	5 1/2 J x 14	5/67/112	30	710	640	200
597.58.063	195/70 R 14	96 N	CR-966	Trailermaxx	5 1/2 J x 14	4/57/100	30	710	640	200
597.58.060	195/70 R 14	96 N	CR-966	Trailermaxx	5 1/2 J x 14	5/67/112	30	710	640	200
599.67.275	205/70 R 14 RF	95 T	MA-701	Maxxis	5 1/2 J x 14	5/67/112	30	690	656	209

RF = Reinforced



Wiel compleet



Artikel-Nr.	Maatvoering	LI	Profiel	Merk	Wiel	Aansluitmaat	ET	Draagvermogen kg	Hoogte mm	Breedte mm
597.72.865	175/65 R 15	92 N	CR-966	Trailermaxx	5 J x 15	5/67/112	30	630	607	177
597.73.175	185/65 R 15	88 T	UA-603	Maxxis	5 1/2 J x 15	5/67/112	30	560	631	197
597.73.285	195/65 R 15 RF	93 N	BK-903	Security	5 1/2 J x 15	5/67/112	30	650	635	201
597.75.600	205/65 R 15 RF	100 N	MA-702	Maxxis	5 1/2 J x 15	5/67/112	30	800	657	212

RF = Reinforced



Speciale complete wielen met lage inbouwhoogte



Artikel-Nr.	Maatvoering	LI	Profiel	Merk	Wiel	Aansluitmaat	ET	Draagvermogen kg	Hoogte mm	Breedte mm
586.92.080	16.5x6.5 - 8	78 M	C-834	Trailermaxx	5.50 x 8	4/57/100	0	425	425	167
586.92.090	18.5x8.5 - 8	78 M	C-834	Trailermaxx	7.00 x 8	4/57/100	0	425	462	213
599.67.217	195/50 - 10	98 N	B-62	Sava	6.00 x 10	5/67/112	-4	750	455	190
599.65.100	195/50 - 10	98 N	M-8001	Trailermaxx	6.00 x 10	4/57/100	0	500	455	190
599.67.216	195/50 - 10	98 N	M-8001	Trailermaxx	6.00 x 10	5/67/112	-4	750	455	190
599.67.206	195/50 - 10	98 N	M-8001	Trailermaxx	6.00 x 10	5/94/140	-4	750	455	190
599.67.229	195/55 R 10 C	98 N		Diverse	6.00 x 10	5/67/112	-4	750	469	192
599.67.227	195/55 R 10 C	98 N	CR-966	Trailermaxx	6.00 x 10	4/60/100	0	500	469	192
599.67.226	195/55 R 10 C	98 N	CR-966	Trailermaxx	6.00 x 10	5/67/112	-4	750	469	192
599.67.224	195/55 R 10 C	98 N	CR-966	Trailermaxx	6.00 x 10	5/94/140	-4	750	469	192
599.67.260	20.5x8.0 - 10	98 N	C-834	Trailermaxx	6.00 x 10	5/67/112	-4	750	500	203
597.19.820	155/70 R 12 C	104 N	VR-307	Vee Rubber	4 1/2 J x 12	5/67/112	0	900	525	163
597.19.821	155/70 R 12 C	104 N	VR-307	Vee Rubber	4 1/2 J x 12	5/67/112	20	900	525	163
597.19.822	155/70 R 12 C	104 N	VR-307	Vee Rubber	4 1/2 J x 12	5/67/112	30	900	525	163
597.19.824	155/70 R 12 C	104 N	UE-168	Trailermaxx	4 1/2 J x 12	5/67/112	0	900	525	163
597.19.825	155/70 R 12 C	104 N	UE-168	Trailermaxx	4 1/2 J x 12	5/67/112	20	900	525	163
597.19.826	155/70 R 12 C	104 N	UE-168	Trailermaxx	4 1/2 J x 12	5/67/112	30	900	525	163
599.95.221	185/60 R 12 C	104 N	CR-966	Trailermaxx	5 1/2 J x 12	5/67/112	30	900	527	185
586.92.160	225/55 R 12 C	104 N	CR-966	Trailermaxx	7.00 x 12	5/67/112	10	900	554	232
597.37.470	195/50 R 13 C	104 N		Diverse	5 1/2 J x 13	5/67/112	30	900	525	198
597.37.450	195/50 R 13 C	104 N	CR-966	Trailermaxx	5 1/2 J x 13	5/67/112	30	900	525	198



C - Wiel compleet



Artikel-Nr.	Maatvoering	LI	Profiel	Merk	Wiel	Aansluitmaat	ET	Draagvermogen kg	Hoogte mm	Breedte mm
596.00.015	140/70 R 12 C	86 N	VTR 313	Vee Rubber	4 1/2J x 12	5/67/112	20	530	509	147
596.00.022	145 R 12 C	86 N	UE-168	Trucmaxx	4 1/2J x 12	5/67/112	20	530	537	147
596.00.032	155 R 12 C	88 N	UE-168	Trucmaxx	4 1/2J x 12	5/67/112	20	560	550	157
596.00.046	155 R 13 C	91 N	TR-603	Security	4 1/2J x 13	4/57/100	30	615	581	157
596.00.048	155 R 13 C	91 N	TR-603	Security	4 1/2J x 13	5/67/112	30	615	581	157
596.00.050	155 R 13 C	91 N	CR-966	Trucmaxx	4 1/2 J x 13	4/57/100	30	615	581	157
596.00.052	155 R 13 C	91 N	CR-966	Trucmaxx	4 1/2 J x 13	5/67/112	30	615	581	157
596.00.113	165 R 13 C	94 N	TR-603	Security	5 J x 13	4/57/100	30	670	596	167
596.00.114	165 R 13 C	94 N	TR-603	Security	5 J x 13	5/67/112	30	670	596	167
596.00.131	175 R 13 C	97 N	UE-168	Trucmaxx	5 J x 13	4/57/100	30	730	612	176
596.00.132	175 R 13 C	97 N	UE-168	Trucmaxx	5 J x 13	5/67/112	30	730	612	176
596.00.144	165 R 14 C	97 N	UE-168	Trucmaxx	5 J x 14	4/57/100	30	730	622	167
596.00.146	165 R 14 C	97 N	UE-168	Trucmaxx	5 J x 14	5/67/112	30	730	622	167
596.00.162	175 R 14 C	99 N	V-22	Vee Rubber	5 1/2 J x 14	4/57/100	30	775	634	178
596.00.117	175 R 14 C	99 N	V-22	Vee Rubber	5 1/2 J x 14	5/67/112	30	775	634	178
596.00.330	185 R 14 C	104 N	CR-967	Trailermaxx	5 1/2 J x 14	5/67/112	30	900	650	194
596.00.340	185 R 14 C	104 N	TR-603	Security	5 1/2 J x 14	5/67/112	30	900	650	194
596.00.512	195 R 14 C	106 N	TR-603	Security	5 1/2 J x 14	5/67/112	30	950	668	198
596.00.513	195 R 14 C	106 N	TR-603	Security	6 J x 14	6/161/205	-5	950	668	198
596.00.705	205 R 14 C	109 N	TR-603	Security	5 1/2 J x 14	5/67/112	30	950	696	204
596.00.725	205 R 14 C	109 N	TR-603	Security	6 J x 14	6/161/205	-5	1030	696	204
596.00.940	215 R 14 C	116 N	TR-603	Security	5 1/2 J x 14	5/67/112	30	950	717	211
596.00.950	215 R 14 C	116 N	TR-603	Security	6 J x 14	6/161/205	-5	1250	717	211
596.00.961	195/70 R 15 C	106 N	TR-603	Security	5 1/2 J x 15	5/67/112	30	950	655	196
596.00.930	205/65 R 15 C	102 N	UE-103	Trucmaxx	6 J x 15	5/67/112	30	950	657	217
596.00.932	205/65 R 15 C	102 N	UE-103	Trucmaxx	6 J x 15	6/161/205	0	1250	657	217
596.00.936	215/70 R 15 C	109 R	UE-168	Trucmaxx	6 J x 15	5/67/112	30	950	695	230
596.00.938	215/70 R 15 C	109 R	UE-168	Trucmaxx	6 J x 15	6/161/205	0	1030	695	230
596.00.972	225/70 R 15 C	116 N	TR-603	Security	6 J x 15	5/67/112	30	950	709	237
596.00.974	225/70 R 15 C	116 N	TR-603	Security	6 J x 15	6/161/205	0	1250	709	237
596.00.630	215/75 R 16 C	113 R	UE-168	Trucmaxx	6 J x 15	5/67/112	30	950	740	225
596.00.632	215/75 R 16 C	113 R	UE-168	Trucmaxx	6 J x 15	6/161/205	0	1150	740	225
596.00.642	225/75 R 16 C	121 N	UE-168	Trucmaxx	6 J x 16	6/161/205	0	1450	744	228



Wiel compleet met aluminium wielen



Artikel-Nr.	Maatvoering	LI	Profiel	Merk	Wiel	Aansluitmaat	ET	Draagvermogen kg	Hoogte mm	Breedte mm
599.67.228	195/55 R 10 C	98 N	CR-966	Trailermaxx	6.00x10 „BK01“	5/67/112	-4	750	469	192
597.38.065	185/65 R 14	93 N	CR-965	Trailermaxx	6J x 14 „B8“	4/60/100	35	560	600	192
597.38.060	185/65 R 14	93 N	CR-965	Trailermaxx	6J x 14 „TM“	5/67/112	30	650	600	192
597.58.065	195/70 R 14	96 N	CR-965	Trailermaxx	6J x 14 „TM“	5/67/112	30	710	640	200
596.00.347	185 R 14 C	104 N	BK-403	Security	6J x 14 „TM“	5/67/112	30	900	650	194
597.72.870	175/65 R 15	92 N	CR-966	Trailermaxx	6J x 15 „B8“	5/67/112	31	630	607	177
597.73.280	195/65 R 15	93 N	BK-403	Security	6J x 15 „B8“	5/67/112	31	650	635	201



Brock TM



Brock B 8



Brock BK 01

Dieplader banden



Artikel-Nr.	Maatvoering	LI	Profiel	Wiel	Aansluitmaat	ET	Draagvermogen kg	Hoogte mm	Breedte mm
599.67.560	205/75 R 17.5	124 M	HN 202	6.00 x 17.5	6/161/205	0	1600	752	205
599.67.570	215/75 R 17.5	135 J	HN 826	6.00 x 17.5	6/161/205	0	2180	760	215
599.67.585	215/75 R 17.5	133 J	HN 826	6.75 x 17.5	6/161/205	128	2060	760	215
599.67.580	215/75 R 17.5	133 J	HN 826	6.75 x 17.5	10/175/225	132	2060	760	215
599.67.590	235/75 R 17.5	143 J	HN 826	6.75 x 17.5	6/161/205	0	2725	793	240
599.67.592	235/75 R 17.5	141 J	HN 826	6.75 x 17.5	8/221/275	128	2575	793	240
599.67.593	235/75 R 17.5	141 J	HN 826	6.75 x 17.5	10/175/225	132	2575	793	240
599.67.595	245/70 R 17.5	143 J	HN 806	6.75 x 17.5	6/161/205	0	2725	789	248
599.67.598	245/70 R 17.5	141 J	HN 806	6.75 x 17.5	10/175/225	132	2575	789	248
599.67.800	265/70 R 19.5	143 J	HN 805	7.50 x 19.5	6/161/205	0	2725	866	258
599.67.820	265/70 R 19.5	143 J	HN 805	8.25 x 19.5	8/221/275	0	2725	866	258
599.67.748	285/70 R 19.5	150 J	HN 805	7.50 x 19.5	6/161/205	0	3350	911	297
599.67.746	285/70 R 19.5	150 J	HN 805	8.25 x 19.5	8/221/275	0	3350	911	297
599.67.790	385/55 R 22.5	160 J	HN 809	11.75 x 22.5	10/281/335	0	4500	996	392
599.67.795	385/55 R 22.5	160 J	HN 809	11.75 x 22.5	10/281/335	120	4500	996	392
599.19.080	385/65 R 22.5	160 J	HN 805	11.75 x 22.5	10/281/335	0	4500	1070	385
599.19.088	385/65 R 22.5	160 J	HN 805	11.75 x 22.5	10/281/335	120	4500	1070	385
599.67.915	425/65 R 22.5	165 J	HN 805	14.00 x 22.5	10/281/335	0	5150	1118	422
599.67.965	445/65 R 22.5	169 J	HN 805	14.00 x 22.5	10/281/335	0	5800	1148	454



Windpower HN 202



Windpower HN 805



Windpower HN 806



Windpower HN 809



Windpower HN 826



Agriband B.V.

Storkstraat 25
3905 KX Veenendaal, Nederland
Tel: +31 (0) 318 - 588588
Telefax : +31 (0) 318 - 588589
info@agriband.nl
www.agriband.nl

Lid van de
Bohnenkamp Groep

Bohnenkamp AG

Dieselstraße 9-13
49076 Osnabrück
Tel.: +49 541 12163-0
info@bohnenkamp.de

Filiaal Landshut

Landshuter Straße 57
84051 Altheim
Tel.: +49 08703 938-0

Filiaal Kletzin

Dorfstraße 93
17111 Kletzin
Tel.: +49 39998 316-0

Bohnenkamp International, s.r.o.

Dolná 2099, 900 01 Modra Slowakei
Tel: +421 33 6486-160
info@bohnenkamp.sk

